

# DP2K-10Sx

Small integrated DLP Cinema® projector for screens up to 10m  
(33 ft) wide



For more information contact Barco

**BARCO**

Visibly yours

# Technical specifications

<b>Digital MicroMirror Device™</b>	3x 0.69" DC2K dark metal devices
<b>Native resolution</b>	2,048 x 1,080 pixels
<b>Housing</b>	Hermetically sealed DMDs and optical assembly
<b>Lamp</b>	2.2kW, short-arc Xenon
<b>Screen size</b>	Up to 10m/33ft wide (screen gain 1.2@14ftl)
<b>Contrast ratio</b>	>1,850:1
<b>Prime Lenses</b>	Fully motorized 1.2-1.7 1.34-1.9 1.5-2.15 1.7-2.55 2.0-3.9
<b>Integrated Media Server (IMS)</b>	JPEG2000 2K & 4K DCI play-out High Frame Rates 3D up to 120 fps (60fps per eye) JPEG 2000 bit-rates up to 500 Mbps Dolby3D color-correction MPEG-2 H.264 2 x 3G-SDI inputs 1 x HDMI 1.4a input (BluRay 3D/4K) 16 x AES/EBU audio channels (2x RJ45) 4 x GPI, 6 x GPO (2x RJ45) 2 x ETH for management & ingest 3 x front-accessible USB for ingest 1 x eSATA port for fast ingest
<b>Integrated storage (IMS)</b>	2 TB effective storage (RAID-5) 3 x hot-swappable 2.5" hard-drives
<b>SMS software (IMS)</b>	Show Player/editor/scheduler Automation, 3D, ingest TMS integration
<b>Projector Diagnostics</b>	Via Communicator control software Via Communicator LITE control software (web-based) Via SNMP agent
<b>Power Requirements</b>	220V
<b>Projector dimensions (HxWxD)</b>	325 x 625 x 910 mm 12.8 x 24.6 x 35.8 inch
<b>Projector weight</b>	Recessed handles for easy carrying 56.5 kg / 125 lbs for carrying (lamp-house removed) (66.5 kg / 147 lbs total weight)
<b>Ambient temperature</b>	35°C / 95° F Max.
<b>Options</b>	ACS-2048 3D add-ons Touch screen monitor Pedestal Auro 11.1 audio decoder license (IMS) Live 3D: RealD LIVE or Sensio Hi-Fi 3D licenses (IMS) RealD ghostbusting license (IMS)